BAS-MOBILIAR

# Concave

RV50FR

**Profile**




Concave inclination





RP50FR




| REF. | | A | B | C | D | H | P | P1 | dm2 | UN. |
|---|---|---|---|---|---|---|---|---|---|---|
| RV30FR | C250 | 365 | 370 | 300 | 300 | 35 | 265 | 265 | 3 | 100 |
| RV40FR | C250 | 440 | 465 | 390 | 390 | 35 | 355 | 355 | 8 | 40 |
| RV50FR | C250 | 525 | 555 | 480 | 480 | 35 | 440 | 440 | 12 | 40 |
| RV60FR | C250 | 660 | 670 | 600 | 600 | 35 | 565 | 565 | 15 | 20 |
| RV70FR | C250 | 760 | 765 | 690 | 690 | 35 | 655 | 655 | 22 | 10 |
| RV80FR | C250 | 845 | 875 | 795 | 795 | 40 | 750 | 755 | 30 | 10 |

Concave is designed to support soft traffic. Perfect for installing on roads with an ADT of 500 to 1.000, particularly hard shoulders and ditches

- Made from spheroidal graphite ductile cast iron, according to ISO 1083 (Type 500-7) and standard EN 1563.
- Compliant with the European standard UNE EN-124.
- PMR grille compliant with laws nos. 2006-1657 and 2006-1658 of 15 January 2007.
- The space between bars is <20mm, which prevents hazards for persons using crutches or wheelchairs.
- Hinged theft-proof cover.
- Elástic1 closure system.
- Metal non-slip surface.
- Coated with non-toxic, non-flammable and non-polluting water-soluble black paint.

V. 2026-09-17 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.