



UM397B  
Bench

# Leman

By Compagnies Desrués © BENITO



Controlled logging



Grey Casting



Hard wood



M10 bolts fixing




**LEMAN designer bench, total dimensions (length x depth) 2300 x 450 mm, made with ductile iron legs (treated with the Ferrus process, the triple-layer protector for iron, which guarantees optimal corrosion resistance). Epoxy primer finish and gray polyester powder paint. Tropical wood planks (treated with a triple-layer Lignus coating, a fungicidal, insecticidal, and water-repellent protector). Stainless steel hardware. Prepared for anchoring with M10 expansion bolts according to surface and project.**

**Optional items not included: Customizable marking with 74x35 mm aluminum plate.**

**Ductile Iron treated with FERRUS:** iron protection process that ensures optimal corrosion resistance. The Ferrus treatment consists of three layers applied after cleaning all dirt and impurities using shot blasting, involving an electrolytic bath followed by an epoxy primer and a final coating of polyester powder paint. Forged black colour

**Hardwood treated with LIGNUS:** Wood from responsible forestry. Density greater than 930kg/m<sup>3</sup>, at 12% humidity, treated with a triple-layer LIGNUS coating, fungicide, insecticide, and water-repellent that provides protection against moisture penetration. Final finish with a layer of natural pigment in a satin finish, which provides additional protection against UV rays, the main cause of deterioration in this type of material.



Ref.	A	B	H	H1
UM397	2300	600	830	420
UM397B	2300	545	450	
UM397S	650	600	830	420

Leman  
UM397S



Leman  
UM397





V. 2026-03-11 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.